AY-U915BT

UHF SMART™ Long-Range UHF-RFID and Rosslare BLE-ID™ Reader







The AY-U915BT is a unique UHF-RFID credential reader with Rosslare BLE-ID™ credential read capability (for both iOS and Android). Installers can configure a wide range of operating parameters using our Rosslare BLE-Admin™ app. AY-U915BT brings a new level of convenience and productivity. The UHF read mode is ISO18000-6C (EPC GEN2) compliant. The reader is suitable for outdoor use in a wide range of RFID applications such as access control, transport management, vehicle management, car parking, and production process control, and works with almost every third-party controller. Choose Rosslare for professional "Security that lasts".

GENERAL DESCRIPTION

By reading both UHF and Bluetooth (BLE), the reader enables system integrators to develop new solutions, such as multi-factor authentication. The AY-U915BT can be configured to read up to 70 credentials within the read range, and to buffer the output to the host controller in Wiegand 26-Bit to 64-Bit or SIA OSDP.

The reader comes with an installation bracket kit for pole mounting, a 5-m-long 10-wire cable, and a switching power supply. The RS-485 OSDP wiring allows a maximum cable distance of 1000 m (3280 ft), and the Wiegand wiring allows a maximum cable distance to the host controller of 150 m (492 ft).

MAIN FEATURES

- MD-81 functionality built in
- Wide range of UHF credential form factors available

- UHF read range up to 6 m (19 ft)
- Supports Bluetooth communication for Rosslare BLE-ID™ smartphone apps for Android and iOS
- Can read up to 10 credentials per second or down
- to 1 credential per second (programmable)

 IP65 for indoor and outdoor use
- RGB LED used for operational indication

PROFESSIONAL GRADE FEATURES

- Supports OSDP reader profile according to v2.1.7 standard from Security Industry Association (SIA)
- Supports mobile Admin app for parameter configuration capability



SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

Operating Voltage Range	9 to 12 VDC (2 A)
Input Current	Standby: 0.2 A max, Read: 1.2 A max
Credential Reading Distance*	Up to 6 m (19 ft) (adjustable) * Read range was tested with Rosslare's LT-UVS-26A-3000 card
BLE-ID Credential Reading Distance*	Up to 12 m (39 ft) (adjustable) – Line of sight. * Read range was tested with iPhone7 and Huawei P10
Transmission Protocol	Wiegand 26-Bit (Custom: Wiegand 34-Bit up to 64-Bit)
Maximum Cable Distance	150 m (500 ft) – Wiegand mode 1000 m (3000 ft) RS-485 – OSDP Mode
Frequency	AY-U915 BT US: 902–928 MHz (America) RFID AY-U915 BT EU: 865–868 MHz (Europe) RFID Bluetooth: 2.402-2.480 GHz
Hopping	The reader uses frequency hopping.
Read Sensitivity	Dual polarization read mode
Cards and Tags	Rosslare's LT-UVS-26A-3000 and LT-UVH-26A-7000 EPC GEN2 (ISO18000-6C) Tags BLE credential using a mobile smartphone
ENVIRONMENTAL SPECIFICATIONS	
Operating Temp. Range	-20°C to 80°C (-4°F to 176°F)
Operating Humidity Range	0 to 95% (non-condensing) Suitable for outdoor use (IP54)
PHYSICAL SPECIFICATIONS	
Dimensions	29.5 x 29.5 x 3.2 cm (11.6 x 11.6 x 1.3 in.)
Weight	Gross: 3.4 kg (7.4 lb); net 2.8 kg (6.2 lb)
SYSTEM COMPONENTS	The AY-U915BT is compatible with standard access controllers. Packaging Includes AY-U915BT with 5-meter pigtail cable, Pole mounting bracket, screw kit, AC/DC 2 Amp power supply (gross).
UHF CREDENTIALS	Please refer to the UHF credentials datasheet for additional details about the compatible UHF credentials.
PRODUCT WARRANTY	2-year limited product warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products manufactures and markets high-quality security products via its worldwide offices and channel partners. Since 1980, Rosslare has offered high-quality systems for enterprise, small business, and residential applications. With Rosslare, you receive the best of all worlds: world-class product engineering and design; professional customer service spanning the globe; and the quality and affordability of a vertically integrated and self-owned manufacturing facility. Our expansive product range features much more than access control solutions and guard patrol management systems; we also offer applications software – such as License Plate Recognition, Time & Attendance, and DVR/alarm integration.

www.rosslaresecurity.com

When installing the UHF credential inside a vehicle, make sure that the vehicle is not RF proof.







