

DS-PS201-WB Wireless Sounder Indoor



- Adjustable volume for alarm, arming, disarming events
- 4 kinds of alarm sounds: FIRE, PANIC, MEDICAL and INTRUSION alarm
- Up to 95 dB at 1 m distance
- Frequency hopping against jamming for reliable transmission



Specification

Communication	
Transmission technology	433.1-433.7 MHz
Transmission range (free space)	Up to 1,200 m
Maximum effective radiated	25 mW max
power (ERP)	23 III VV III dA
Radio signal modulation	2GFSK
Software features	
Temperature indicator	Yes
Indication	
Indication method	Acoustic and LED
Sound volume level	Adjustable, 80-95 dB at a distance of 1 m
Alarm duration	Adjustable, 10 s-15 min
Hardware features	
Tamper-Proof	Yes
Electrical characteristics	
Power supply	4 × AA batteries
Power consumption	max current: 400 mA
	quiescent current: 35 uA
Battery life	Up to 2 years (standby time)
General	
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90%
Dimension(WxHxD)	93 × 93 × 33.7 mm
Weight	117 g

Available Model

DS-PS201-WB



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision Corporate Channel



6 hikvisionhq