

# C3A<sub>\$</sub>W2D

HD 1080p Wire-Free Security Kit

## Security Has Never Been This Easy

With a long-lasting 5,500 mAh rechargeable battery and 100% wire-free design, the standalone C3A can be placed anywhere you need it to go. With the help of the W2D, battery life lasts even longer.



# C3A

100% Wire-Free, Battery-Powered Camera





PIR Motion Detection



1080p



5500 mAh Rechargeable Lithium Battery



Two-Way Talk



125° Diagonal Field of View



IP65 Dust and Water Protection



Night Vision Up to 25 ft. (7.5 m)



2.4GHz



Supports MicroSD Card (Up to 128 GB)

## W2D

Base Station for the C3A






Supports up to six C3A units




Prolongs battery life of connected C3A




Supports 100-decibel siren





## Extra Protection with Accurate Detection

The C3A's passive infrared (PIR) motion detection feature sends you an instant alert with images and videos captured when a visitor approaches. Once you connect the C3A with the W2D, the W2D will even emit a 100-decibel siren when triggered, reminding you to check on what's happening.



### Worry Less with Longer Battery Life

The C3A equips with a removable and rechargeable 5,500 mAh Lithium battery. Paired with the W2D, the C3A's battery life can last even longer.

### **Easy Pairing**

With one-click sync buttons, the C3A and W2D will pair in seconds.



## Comprehensive Accessories to Choose From

A wide range of accessories are also available to enhance your experience, including a charging station, rechargeable battery and mounting bracket for long-lasting protection and good usability.



## Multiple Storage Solutions

Save your recordings with flexible and secured solutions. The C3A comes with a built-in MicroSD card slot that can store up to 128 GB of recorded footage. You can also save your images to EZVIZ Cloud for additional back-up.

(Cloud storage service is only available in certain markets. Please verify the availability before making any purchase.)



Supports MicroSD Card



Encrypted Cloud Storage

## Specifications C3A Model C3A

#### **System Parameters**

Processor High-Performance Embedded SOC Processor

Operation System Embedded RTOS

#### **Camera Parameters**

Sensor 1/4" 2-Megapixel sensor

Lens 2.2mm@F2.4

Field of View Diagonal FOV 125°

Night Vision Up to 25 ft.

#### **Video Parameters**

Compression Standard Smart H.264

Max. Resolution  $1920 \times 1080$ , FHD

Frame Rate Max. 15fps

Adaptive frame rate of network transmission

DNR 3D DNR WDR DWDR

BLC Support

#### **Audio Parameters**

Audio Input Built-in Omni-direction microphone

Audio Output Built-in loudspeaker

Audio Quality Noise suppression

#### **Network Parameters And Storage**

Wireless Built-in 2.4 GHz

Network Configuration AP Pairing
Minimum Network 2 Mbps

Requirements

Local Storage Support microSD card (Up to 128 GB)

Cloud Storage EZVIZ Cloud Storage

#### **Event**

Sensor PIR Motion Sensor

Alarm Customized Alert Area

Siren N/A

#### General

Power Supply 5500 mAh Rechargeable Lithium Battery and 5V DC

Power Consumption Max. 5W Weatherproof IP65

Product Dimensions (inch) 2.2 x 2.8 x 3.6
Packaging Dimensions (inch) 4.7 x 5.1 x 8.5

Weight (lb) 0.47

## Specifications W2D Model CD-W2D-NAM

128 MB

Network Interface
1 RJ-45 10/100Mbps Self-adaptive Ethernet WAN interface.
Minimum Network Environment
2Mbps
Wireless Interface
Supports 2.4GHz Wi-Fi connection.
Battery Camera
Supports up to 6 Wire-Free Cameras
CPU
Qualcomm @ 650 MHz (Maximum)
RAM

#### Flash

16 MB

#### Alarm Siren

Built-in 100dB Siren

#### Antenna

2.4GHz: 2 internal @ 2dB max.

#### Indicator

One System LED. One WAN Port LED.

#### **Button**

One SYNC button. One Power button. One Reset button, hold 10 seconds to RESET.

#### General

DC 5V 2A, Power

typical power consumption < 10watts

The adapter supports a wide voltage range,

expected 100V~240V

4.7 x 5.1 x 8.5

Product Dimensions (inch) 3.7 x 3.7 x 4.3 Packaging Dimensions (inch)

0.4 lb Weight (lb)

## Package Contents:

#### C3A

- Camera
- Battery
- Magnetic Mount
- 3.3-Foot (1-Meter) USB Cable
- Power Adapter
- Screw Kit
- Quick Start Guide

#### W2D

- Base
- 5-Foot (1.5-Meter) USB Cable
- Power Adapter
- 3.3-Foot (1-Meter) Ethernet Cable
- Quick Start Guide

## Requirements

#### C3A

- Operating Conditions: -4°F - 113°F (-20°C - 45°C), Humidity 95% or less

#### W2D

- Operating Conditions: 32°F - 104°F (0°C - 40°C), Humidity 10%-90%

### Certificates

#### C3A

- CE/FCC/UL/IC

#### W2D

- FCC/UL/IC